Selectronic

DATA SHEET

Accessories: High voltage connectors series 22



Multipole connectors for voltages up to 10,000 V and currents up to 30 A.

1 CONNECTOR - 117.645 POSSIBILITIES

- + completely individually pluggable
- + multi-pole (up to 14)
- + allows coding of applications with multiple connectors
- + combines high voltage, low voltage and compressed air

Description:

The multi-pole individually assemblable high-voltage connectors ST / BU series 22 find their application when high voltages are transmitted in connection with high currents. They are available in different versions and are suitable for internal use in the control cabinet as well as for use in device connections. Suitable accessories are also available.

HOUSINGS FOR PLUG/SOCKET MODULES

Housings				
	Grommet housing TG 22 with lateral outlet suitable for installation housing FG 22	76 80 80 446 46 46 46 46 46 46 46 46 46 46 46 46		
	Grommet housing TG 23 with outlet at the rear suitable for installation housing FG 22	91 76		
	Installation housing FG 22 suitable for grommet housing TG 22/23	160 		
	Cable gland TG 22-k suitable for grommet housing TG 22/23			
	Tube fitting TG 22-s suitable for grommet housing TG 22/23			

electronic

DATA SHEET

Accessories: High voltage connectors series 22

FRAMES FOR PLUG/SOCKET MODULES

Frames		
	Frame for plug ST 22	
and an analysis	suitable for grommet housing TG 22/23	
and a second	Frame for socket BU 22	
	suitable for installation housing FG 22	

PLUG/SOCKET MODULES

High-voltage module				
All a	Number of poles	2		
	Module for plug ST 22-h	Connection technology	solder	
21 22-11	31 22-11	Connection cross-section	2.5 mm ² (0.004 in ²)	
Module for sock		Operating voltage	12 kVDC	
	Module for socket BU 22-h	Test voltage	18 kVDC	
	DU 22-11	Max. current	30 A AC	
Pneumatic module	,			
	Module for plug	Number of poles	2	
ST 22-p	ST 22-p	Connection technology	Hose connection	
	Module for socket	Hose diameter (internal)	4 mm (0.157 in)	
	BU 22-p	Operating pressure	8 bar	
Mains insert incl. conta	ct plug/socket (1 set =	•		
	Plug insert	Number of poles	10	
	ST 22-n	Connection technology	solder	
	Contactpl.: KS 22-e	Connection cross-section	0,14 - 2,5 mm ² (0.002 - 0.004 in ²)	
	Socket insert	Operating voltage	400 V	
	BU 22-n	Max. current	16 AAC	
	Contactso.: BB 22-e	Contact plug/socket availa	ble as spare part.	
Dummy socket				
	Module for plug ST 22-x			
	Module for socket BU 22-x			